

Onika Paints

NuTec Coat

WATERPROOF DECORATIVE
COATINGS FOR EXTERIOR
SURFACE.

NuTec Coat is a water based polymer wall coating with high quality acrylic emulsion for exterior masonry surface. It forms a higher film thickness on the surface providing tough waterproof membrane ensuring no ingress of water through substrate.

BENEFITS:

- Provides a high quality effective waterproofing cum colour coating for exterior walls
- Forms High build film with proper elongation & flexible property makes uniform waterproof over surface.
- Breathable property of dry film has better permeability to stay longer against internal wall moisture.
- Elastomeric property accommodates thermal movement of hair line cracks
- Excellent resistance to UV rays for outstanding durability
- Resistance to dirt pick up and resistance to Algae & Fungus growth on the coated surface for longer period.
- Can be tinted to any pastel shade with universal strainers.
- Excellent protection against chloride, sulphate & water vapour penetration from atmosphere.
- User friendly product and can be easily applied by brush, rollers or spray.



APPLICATION METHOD:



Clean the surface thoroughly with water & remove the flakes of old paints or lime wash.



Dilute Unika Paints NuTec Coat up to 20% with water and mix thoroughly.



Apply 2 coats on surface previously applied with wall primer. A gap of 4 to 6 hrs should be given between the coats. If necessary, third coat should be applied for good opacity.

USES:

Unika Paints NuTec Coat is a ready to use product and suitable for use on all types of concrete structures, Asbestos sheets, sloping roofs, brick walls etc., it is also suitable for application on previously painted surface.



TECHNICAL SPECIFICATION:

SHADE	:	White & light base
DRYING TIME	:	1 Hour
RE-COATING TIME	:	4 hrs @ 30°C
DRY FILM THICKNESS	:	120 microns in two coats
ELONGATION AT 120 MICRONS	:	>100%
COVERAGE	:	30-40 sq.ft. in 2 coats on smooth surface (It may vary depending upon substrates)
NO. OF COATS RECOMMENDED	:	2-3 coats depending on work & site conditions
UV RESISTANCE	:	Good
RESISTANCE TO CHLORIDE, SULPHATE IONS & CARBONATION	:	Good
RESISTANCE TO ALGAE & FUNGI	:	Excellent for more than 5 yrs
SHELF LIFE	:	1 year in sealed containers



AVAILABLE PACKAGING SIZES:	1L	4L	10L	20L
----------------------------	----	----	-----	-----