

Onika Paints

ns  
NuTecSol

# NuTec Wall Putty

WHITE CEMENT BASED WALL CARE PUTTY.

White Cement Based wall care putty with effective polymers for application on interior and exterior rough plasters to give a smooth finish.


## BENEFITS

- Provides excellent filling capacity with smooth and uniform finish
- Good workability & Faster drying
- Offers smooth glossy finish with good water resistance
- Good tensile adhesion strength and excellent abrasion resistance
- Enables good intercoat adhesion to all emulsion paints.
- Better adhesiveness and durability, which increases the life of paints
- Does not require any curing after application and prevents growth of algae & fungi



## COVERAGE

On rough masonry surface by putty knife.



## 2 COATS

10 Sq.ft/Kg for up to 1.5 -2mm thickness in 2 coats.

## INSTRUCTION FOR USE:

- Ensure the surface is completely free from all dirt, loosely held plaster, powdery residue, oil, grease or any other contamination. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- Sand the surface with sand paper
- Pre wet the surface before application of first coat
- Mix wall care putty with 30 to 40% water or as required to suit for application
- Apply first coat and fill the dents using knife/trowel
- Allow drying time of 5-6hrs and apply second coat
- Apply coat of primer followed by coats of emulsion

DRYING TIME TO RECOAT 6-8 HOURS

## TECHNICAL DETAILS:

Drying time	Surface dry time 30 min
Sheen levels	NA
Flash point IS101/1987 Part 1, Sec 6	NA
Stability of thinned paint	To be used within 45 minutes

AVAILABLE PACKAGING SIZES:				
	1kg	5kg	10kg	20kg



## RECOMMENDED USAGE

