

# Unika Paints Amaze

WATER BASED ACRYLIC COATING  
FOR EXTERIOR SURFACE.

ns  
NuTecSol

Unika Paints Amaze is a water based polymer wall coating with high quality acrylic emulsion for exterior masonry surface. It forms a higher film thickness on the surface.

#### BENEFITS:

- Provides high quality smooth finish and colour coating for exterior walls
- Makes brighter, clean shades that will not lose properties for long time
- Excellent classy finish to make walls beautiful
- Better coverage and smoothness guaranteed at every time of application with superior finish.
- Surface withstands extreme tropical climatic conditions and fungus formation
- Offers excellent resistance to UV radiations


GRADES  
AVAILABLE:

PREMIUM  
SUPREME  
ULTRA




## COVERAGE:

On normal masonry surface after brushing



### 1 COAT

100 - 130 sq.ft/ltr\*\*



### 2 COAT

55 - 65 sq.ft/ltr\*\*

\*\*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

## HOW TO APPLY



Clean the surface thoroughly with water & remove the flakes of old paints or lime wash



Apply 2 coats of Amaze on surface previously applied with wall primer. A gap of 4 to 6 hrs should be given between the coats. If necessary, third coat should be applied for good quality



Dilute Amaze up to 20% with water and mix thoroughly

## TECHNICAL DETAILS

Drying time	Surface dry time 30 min
Sheen levels	3 - 12 at 60 deg GH
Flash point IS101/1987 Part 1, Sec 6	NA
Stability of thinned paint	To be used within 24 hours



AVAILABLE PACKAGING SIZES:	1L	4L	10L	20L
----------------------------	----	----	-----	-----

Manufactured and marketed by  
**NuTecSol Products India Pvt, Ltd.,**

Plot No. 63A, KIADB Industrial Area Phase 2,  
Antharasanhalli, Tumkur-572106, Karnataka

An ISO: 9001 : 2015 Accredited Company

+91 83103 17294 | +91 86602 58402  
info@nutecsol.in | www.nutecsol.com