

Unika Paints Snowsil

ACRYLIC BASED WALL PUTTY.

Unika Paints SnowSil acrylic based wall Putty. It is one of the best products of it's kind available in the market, provides a very strong, durable foundation and brings out the best performance from the finish paints, both in looks and in durability.


BENEFITS

- Provide smooth and uniform finish to rough plasters
- Good work ability
- Does not require curing with water
- Resists growth of algae and fungi on wall
- Good undercoat adhesion to emulsion paints




COVERAGE

On primed masonry surface by putty knife.



1 COAT
38 - 44 sq.ft/kg**



2 COAT
24 - 35 sq.ft/kg**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

HOW TO APPLY



PLASTER new masonry surfaces must be allowed to cure completely for best results. It is recommended to allow 28 days as curing time for new masonry



CLEANING Ensure that surface is completely free from all dirt, loosely held plaster, powdery residue, oil, grease or any other contamination. Any previous growth of fungus, algae moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water



FILLING FOR CRACKS For filling cracks upto 3mm use NuTec Crack Fill



PRE WETTING Pre wet the surface with water before application of 1st coat of SNOWSIL

TECHNICAL DETAILS

Drying time	Surface dry time 30 min
Sheen levels	15-35 at 35 deg GH
Flash point IS101/1987 Part 1, Sec 6	NA
Stability of thinned paint	To be used within 24 hours

AVAILABLE PACKAGING SIZES:				
	1kg	5kg	10kg	20kg



Manufactured and marketed by
NuTecSol Products India Pvt, Ltd.,

Plot No. 63A, KIADB Industrial Area Phase 2,
Antharasanahalli, Tumkur-572106, Karnataka

An ISO: 9001 : 2015 Accredited Company

+91 83103 17294 | +91 86602 58402

info@nutecsol.in | www.nutecsol.com